

Technical drawing of a mechanical part, showing three views: front view, top view, and side view.

Front View (Top Left):


- Overall diameter: $\phi 159$
- Flange thickness: 120
- Central bore diameter: P.C.D. $\phi 130$
- Flange holes: 4 $\phi 8.5$ 贯穿 (4 $\phi 8.5$ through holes)
- Angle: 45°

Top View (Bottom Left):

- Overall width: 28
- Internal width: 8
- Internal width: 25
- Thread: M10

Side View (Right):

- Overall length: 284.5
- Flange thickness: 50
- Internal length: 229
- Internal length: 105
- Internal diameter: $\phi 110g6$
- Internal diameter: $\phi 35$
- Internal diameter: $\phi 25h6$
- Internal diameter: $\phi 120$
- Internal diameter: $\phi 22G6$
- Internal diameter: $\phi 110G6$
- Internal length: 55.5
- Internal length: 18
- Internal length: 49
- Internal length: 45
- Internal length: 7
- Internal length: 64
- Internal length: 169
- Internal length: 9.28

<div>客户签字</div> <div>Customer's Signature</div>	速 比 Ratio	15-100	运转效率 Transmission Efficiency	94%	角法 Angle method	第三视角 Third perspective	公司名称	 锋桦 锋桦传动科技(江苏)有限公司 锋桦传动設備(上海)有限公司 台灣 鋒 桦 科 技 有 限 公 司
	额定扭矩 Rated Torque	141-165N·m	精度寿命 Service Life	20000Hrs	单位 Unit	mm	Company name	
	最大扭矩 Max.Torque	423-195N·m	噪音 Noise	67dB	比例 Proportion	1:1	图名 Drawing name	行星减速机Planetary gearbox: PFR-120-L2-S2-P2
	额定输入转速 Rated Input speed	3000rpm	环境温度 Enviromental	-15° -- +90°	版本 Version	最新版本 Latest version	服务热线 Service hotline	400-8040-668 / QQ:4008040668
	最大输入转速 Max.inputspeed	5000rpm	惯量 Inertia	12.03	日期 Date	2020.02.23	網址/郵箱Website/email	www.fht.tw / www.3fgearmotor.com fht@fht.tw / sales@3fgearmotor.com
	回程间隙 Backlash	≤13arcmin	重量 Weight	6.92Kg	设计 Design	设计 Design	電話/傳真Tel./Fax	021-39948832 /021-39948836